

# JARVIS

## Multi-Purpose Spring Balancers



**The Lift that Never Lets You Down!**

**JARVIS MAKES IT HAPPEN**

## Weight Range 2 - 22 lbs / 1 - 10 kg

### FEATURES

- Safety devices to prevent load dropping - due to spring breakage
- Precision guided, stainless steel cable prevents entanglements and jamming
- Operator controlled locking devices
- Visible cable inspection
- Easy tension adjustment



Model No.		4042033	4042040	4042043	4042044	4042045
Weight Range	lbs	4 - 9	13 - 18	2 - 6	9 - 13	18 - 22
	kg	2 - 4	6 - 8	1 - 2.5	4 - 6	8 - 10
Cable Ext.	ft	7	7	7	7	8
	m	2	2	2	2	2.5
Dimensions	in	8 x 6 x 4	8 x 6 x 4	8 x 6 x 4	8 x 6 x 4	8 x 6 x 4
	cm	20 x 15 x 10	20 x 15 x 10	20 x 15 x 10	20 x 15 x 10	20 x 15 x 10
Net Weight	lbs	4.2	6	4	5	8
	kg	2	2.5	2	2.3	3.7

## Weight Range 22 - 49 lbs / 10 - 22 kg

### FEATURES

- Safety devices to prevent load dropping - due to spring breakage
- Inert spring drum assembly
- Locking device to secure load at any height
- Worm screw adjustment
- Upper rotary suspension with safety hook



Model No.		4042035	4042037	4042046
Weight Range	lbs	40 - 49	22 - 31	31 - 40
	kg	18 - 22	10 - 14	14 - 18
Cable Ext.	ft	7	7	7
	m	2	2	2
Dimensions	in	17 x 8 x 7	17 x 8 x 7	17 x 8 x 7
	cm	43 x 20 x 18	43 x 20 x 18	43 x 20 x 18
Net Weight	lbs	13	12	14
	kg	6	5	6.5

## Weight Range 49 - 99 lbs / 22 - 45 kg

### FEATURES

- Safety devices to prevent load dropping - due to spring breakage
- Adjustable stroke limiting device
- Locking device to secure load at any height
- Worm screw adjustment
- Upper rotary suspension with ball bearing



Model No.		4042034	4042039	4042047	4042048
Weight Range	lbs	49 - 55	55 - 77	55 - 66	77 - 99
	kg	22 - 25	25 - 35	25 - 30	35 - 45
Cable Ext.	ft	7	10	7	7
	m	2	3	2	2
Dimensions	in	17 x 8 x 7	24 x 13 x 13	18 x 11 x 11	18 x 11 x 11
	cm	43 x 20 x 18	61 x 33 x 33	46 x 28 x 28	46 x 28 x 28
Net Weight	lbs	15	46	25	27
	kg	6.6	21	11.5	12.4

## Weight Range 99 - 165 lbs / 45 - 75 kg

### FEATURES

- Rugged ribbed and sealed monoblock aluminum construction
- Auxiliary safety suspension
- Safety device against load dropping
- Upper rotary suspension with safety hook
- Stainless steel cable with anti-friction cable guide



Model No.		4042036	4042042	4042049	4042050
Weight Range	lbs	121 - 143	110 - 132	143 - 165	99 - 121
	kg	55 - 65	50 - 60	65 - 75	45 - 55
Cable Ext.	ft	7	10	7	7
	m	2	3	2	2
Dimensions	in	18 x 11 x 11	24 x 13 x 13	18 x 11 x 11	18 x 11 x 11
	cm	46 x 28 x 28	61 x 33 x 33	46 x 28 x 28	46 x 28 x 28
Net Weight	lbs	30	56	32	28
	kg	13.6	25.3	14.5	12.5

## Weight Range 132 - 198 lbs / 60 - 90 kg

### FEATURES

- Rugged ribbed and sealed monoblock aluminum construction
- Locking device to secure load regardless of height
- Safety device against load dropping
- Upper rotary suspension with safety hook
- Rotary upper hook with ball bearing



Model No.		4042038	4042051
Weight Range	lbs kg	176 - 198 80 - 90	132 - 154 60 - 70
Cable Ext.	ft m	10 3	10 3
Dimensions	in cm	24 x 13 x 13 61 x 33 x 33	24 x 13 x 13 61 x 33 x 33
Net Weight	lbs kg	64 29	60 27



Jarvis' World Headquarters Building in Middletown, CT U.S.A.

Please contact:

Jarvis Products Corporation

33 Anderson Road

Middletown, CT 06457- 4926

United States of America

Tel; 860 347-7271

Fax: 860 347-9905

E-mail: [jarvis.products.corp@snet.net](mailto:jarvis.products.corp@snet.net)

Web site: [www.jarvisproducts.com](http://www.jarvisproducts.com)